



Signature RC
Colours that Count

78 Joshua Moore Dr,
Horningssea Park, NSW 2171
A.B.N 15 070 040 614
Phone: 0406074 378
0424 247 850

Technical Data Sheet

Date of Issue: 20/05/08

Item Code: CFX001

Item Name: ChromeFX – MultiChrome

Before You Begin

Read instructions thoroughly. This product is for personal airbrush use only and not recommended for any other use. This data sheet has been prepared to inform our customers about the products properties. Since we cannot control the application or preparation, the user should make appropriate tests to check the suitability of the product. Surface preparation must be properly carried out prior to painting. Always use a quality compressor, suitable airbrush, facial mask and appropriate clothing. SignatureRC does not recommend painting in cold temperatures (below 21.c) or mixing and using incompatible products, possibly from other manufacturers, which may cause problems.

1. Description:

ChromeFX – Multichrome is a highly reflective Chrome look unlike any other! Our easy to follow technical data sheet shows you how to apply Multichrome with consistent results every time! Multichrome is a versatile paint which can be applied using any standard or high quality personal airbrush and dries instantly to a mirror-like finish. ChromeFX - Multichrome is perfect for eye-catching pin stripes and effective line accents and can be used on various forms of lexan, perspex, plastic, metal and is extremely effective in conjunction with 'Candys'.

The key to achieving the highest mirror-like reflectivity lies in the surface preparation. You must ensure that the surface is clean, dry, static free and has no possible residue. Carefully follow these steps for the best results.

2. Product Data:

Theoretical coverage: An entire 1/10th shell per 30ml

3. Substrates & Preparation:

Surface must be clean and dry with no chemical residue and static free.

4. Application:

a) Mixing Ratio/Reducing: Product is ready to use, no extra thinning is required. Shake contents vigorously before use.

b) Recommend Air Pressure: We recommend that you lower your air pressure to between 10-18psi. We would also recommend using a 0.3 - 0.5 needle tip combination.

c) Standard Application Guide:

1. Apply the Multichrome using a personal airbrush, apply in even and very light 'dusting' coats and allow to thoroughly dry between coats. The best results are achieved with 2 - 3 coats.
2. Allow to dry thoroughly for 5 minutes.
3. Immediately back with a BLACK spirit or water based paint.

NOTE:

Only apply Multichrome at temperatures of 20.c -30.c. Do not apply in humid conditions.

We recommend using our PrepFX Residue Remover to ensure a clean surface before applying Multichrome.

Uneven applications will result in 'tram tracks', blotchiness and an undesirable finish.

This is not like any other paint, trying to obtain a full coverage in a single pass will result in a poor finish. DO NOT apply too much material.

5. Cleaning Equipment:

After use, clean equipment thoroughly with thinners.

6. Storage Period & Conditions:

1 year when in cool, dry conditions.

As this is classed as a Multichrome, varying from the application guide will produce differing results. Please see the SignatureRC website for further variations.

www.signaturerc.com