



Signature RC
Colours that Count

78 Joshua Moore Dr,
Horningssea Park, NSW 2171
A.B.N 15 070 040 614
Phone: 0406074 378
0424 247 850

Technical Data Sheet

Date of Issue: 20/05/08

Item Code: SFX650

Item Name: SpecialFX - LunatiX

Before You Begin

Read instructions thoroughly. This product is for personal airbrush use only and not recommended for any other use. This data sheet has been prepared to inform our customers about the products properties. Since we cannot control the application or preparation, the user should make appropriate tests to check the suitability of the product. Surface preparation must be properly carried out prior to painting. Always use a quality compressor, suitable airbrush, facial mask and appropriate clothing. SignatureRC does not recommend painting in cold temperatures (below 21.c) or mixing and using incompatible products, possibly from other manufacturers, which may cause problems.

1. Description:

Read instructions thoroughly. This product is for use in conjunction with personal airbrushing and spray cans and is not recommended for any other use. This data sheet has been prepared to inform our customers about the products properties. Since we cannot control the application or preparation, the user should make appropriate tests to check the suitability of the product. Surface preparation must be properly carried out prior to painting. Always use a quality compressor, suitable airbrush, facial mask and appropriate clothing. SignatureRC does not recommend painting in cold temperatures (below 21.c) or mixing and using incompatible products, possibly from other manufacturers, which may cause problems.

2. Product Data: Theoretical coverage: Varies upon application method.

3. Substrates & Preparation: Surface must be clean and dry with no chemical residue.

4. Application:

a) Mixing Ratio/Reducing: Product is ready to use, reducing is not required. Do not dilute.

b) Standard Application Guide:

1. Apply liberally with a soft haired brush to the required area, ensure to coat the unmasked area with medium, wet coats.
2. Allow to dry thoroughly, usually within 10-15 minutes at temperatures of 20.c-25.c.
3. Apply 2 very light "dusting" coats of a contrasting SPIRIT/SOLVENT based paint (we recommend black in most cases). NOTE: ONLY SPIRIT/SOLVENT BASED paint can be used here!
4. Once the spirit based paint has dried, saturate a sponge with tap water and wipe away the crystallization with gentle rubbing. Continue until all LunatiX formation is removed, rinsing sponge frequently.
5. Now apply your main colour choice over the area as you normally would. Spirit and water based paints are both compatible by this stage. Allow to dry thoroughly for 5 minutes.

NOTE:

Warmer temperatures will result in the SpecialFX - LunatiX forming in longer and wider sweeping fractures, and cooler temperatures will result in finer crackles. Holding the Lexan shell for a lengthy period of time can interfere with the surface temperature of the Lexan.

SpecialFX - LunatiX can be applied with a clean lint free cloth soaked with LunatiX in slow even motions. Be sure to meet edges and any masked off areas liberally.

If the LunatiX solution beads up, this means there is surface contamination, simply clean and dry the area thoroughly and start over.

This effect is random, and patterns are a result of application and situation. To replicate ensure to match application and conditions.

If you do not like the formation that is achieved simply wash off with water, rinse and dry thoroughly and start over.

DO NOT use water based paints directly onto the SpecialFX - LunatiX. Water based paints will reactivate the LunatiX and it WILL NOT work. Only apply water based paints AFTER the LunatiX has been wiped/rubbed away completely.

This product does not work in conjunction with ordinary masking tapes as it is water based and will damage the tape and cause significant bleed throughs. We recommend using SignatureRC EZMask or QikMask.

5. Cleaning Equipment: After use, clean equipment thoroughly with thinners.

6. Storage Period & Conditions: 1 year when in cool, dry conditions.

As SpecialFX - LunatiX can be easily influenced and manipulated into specified styles/formations, please visit the SignatureRC website for further variations of application.

www.signaturerc.com